

概述 Summary

- > 单组输出: 功率1200W
Single output: power 1200W
- > 输入电压: 100~132VAC/200~264VAC 由开关切换
Input voltage: 100~132VAC/200~264VAC by switch



常见规格 General Specification

291 × 132 × 68mm

| 性能 Specification | 型号 Model | S-1200-12 | S-1200-24 | S-1200-36 | S-1200-48 |
|---|----------|--|-----------|-----------|-----------|
| 直流输出电压、电流 DC output voltage, current | | 12V 0~100A | 24V 0~50A | 36V 0~33A | 48V 0~25A |
| 纹波及噪音 Wave and noise | | 150mVp-p | 180mVp-p | 180mVp-p | 240mVp-p |
| 进线稳定度 Inlet wire stability | | ±0.5% | ±0.5% | ±0.5% | ±0.5% |
| 负载稳定度 Load stability | | ±0.5% | ±0.5% | ±0.5% | ±0.5% |
| 效率 Efficiency | | 80% | 85% | 85% | 87% |
| 直流电压可调范围 Adjustable range for DC voltage | | ±10% | ±10% | ±10% | ±10% |
| 输入电压范围 Input voltage range | | 100~132VAC/200~264VAC 由开关切换 254~370VDC 47~63Hz 100~132VAC/200~264VAC by switch 254~370VDC 47~63Hz | | | |
| 冲击电流 Impact current | | 冷启动电流 Cold start current 45A/230VAC | | | |
| 过载保护 Overload protection | | 105%~135%切断输出, 自动恢复 105%~135% cut off the output, automatic recovery | | | |
| 启动、上升、保持时间 Setup, rise, hold up time | | 2000ms, 50ms, 20ms/230VAC 满负载 at full load | | | |
| 耐压性 Withstand voltage | | 输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute | | | |
| 隔离电阻 Isolation resistance | | 输入输出间 输入与外壳间 输出与外壳间: 500VDC/100M Ω I/P-O/P I/P-FG O/P-FG: 500VDC/100M Ω | | | |
| 工作温度 Working temperature | | -10°C ~ +50°C | | | |
| 尺寸 Dimension | | 291 × 132 × 68mm | | | |
| 重量 Weight | | 2.65kg | | | |
| 包装 Packing | | 37.5 × 31 × 25.5CM/6PCS/16kg | | | |

外形尺寸 Overall dimension(mm)

